





Slashed Strip Block- Aug BoM 2022

Kit contains: 5 x 2 1/2" Pastel Strips & 1 x 1 1/2" Thin Strip

The block **will** end up rectangular shaped, but do not trim.

<ol style="list-style-type: none"> 1. Sew the pastel strips together along the long edge, matching one short edge and leaving the other edge uneven. 2. Press all seams the same way. 	
<ol style="list-style-type: none"> 3. Mark 2" along top long edge and 8" along bottom long edge. 4. Slash pieced block along a line at an angle between the two marks. 	
<ol style="list-style-type: none"> 5. Place the thin strip right side down on the first piece, leaving extra fabric on both ends and sew 1/4" seam. 6. Press seam towards the thin strip. 	
<ol style="list-style-type: none"> 7. Mark the edge of the thin strip with a pin in line with the top edge of the first piece. 8. Place the second piece right side down along the thin strip, with the point a 1/4" above the pin. 9. Sew 1/4" seam taking extra care not to stretch the second piece. 10. Press seam towards the thin strip 	





Do not cut off any extra fabric, I will trim the finished block and use the extra pieces.



Slashed Strip Block- Aug BoM 2022

Kit contains: 5 x 2 1/2" Pastel Strips & 1 x 1 1/2" Thin Strip

The block **will** end up rectangular shaped, but do not trim.

<ol style="list-style-type: none"> 11. Sew the pastel strips together along the long edge, matching one short edge and leaving the other edge uneven. 12. Press all seams the same way. 	
<ol style="list-style-type: none"> 13. Mark 2" along top long edge and 8" along bottom long edge. 14. Slash pieced block along a line at an angle between the two marks. 	
<ol style="list-style-type: none"> 15. Place the thin strip right side down on the first piece, leaving extra fabric on both ends and sew 1/4" seam. 16. Press seam towards the thin strip. 	
<ol style="list-style-type: none"> 17. Mark the edge of the thin strip with a pin in line with the top edge of the first piece. 18. Place the second piece right side down along the thin strip, with the point a 1/4" above the pin. 19. Sew 1/4" seam taking extra care not to stretch the second piece. 20. Press seam towards the thin strip 	

Do not cut off any extra fabric, I will trim the finished block and use the extra pieces.

